

TECHNICAL DETAILS

The tables below show the general specifications for the TRITON 660/9 AVA. Additional items can be ordered as options. Details can be found in our equipment tier.

GENERAL

Depth	6 ft / 200 m
Passengers	1 Pilot + 8 Adults / 1 Pilot + 6 Adults & 4 Children
Payload	1,697 lb / 765 kg
Min. Payload	1,135 lb / 515 kg
Speed	3 kn
Endurance	12 hours
Hatch Inner ø	23.6 in / 600 mm

SIZE & WEIGHT

Length	9. ft / 2, mm
Width	14.8 ft / 4,500 mm
Height	7.55 ft / 2,300 mm
Weight	2 0 lb / 1 00 kg
Dynamic Passenger Compensation Ballast	550 lb / 250 kg
Variable Ballast	550 lb / 250 kg
Pressure Hull Internal Volume	6,300 l

SYSTEMS

24 V Supply	Dual Supply + Emergency
Main Battery	57 kWh
Main Thrusters	4 x 5.5 kW
Maneuvering Thrusters	4 x 5.5 kW
Control	Joystick, Touchscreen & Manual Override
External Lights	8+ x 20,000 lumen LED
Life Support	Oxygen & CO ₂ Scrubber



+1 (772) 770-1995

+1 (772) 589-1011

info@tritonsubs.com

